NSN 5310-00-779-4578

Gang Channel Self-locking Nut Assembly - Page 1 of 2



| , , |
|---|
| View Online at https://aerobasegroup.com/nsn/5310-00-779-4578 |
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Radius: |
| 10.140 inches |
| Overall Width: |
| 0.490 inches |
| Nut Style: |
| Gang channel, self locking |
| Removable Nut Manufacturer Code: |
| 56878 |
| Channel Style: |
| Radius type |
| Assemblyheight: |
| Between 0.334 inches and 0.351 inches |
| Channel Height: |
| 0.130 inches |
| Nut Spacing: |
| 1.593 inches |
| Removable Nut Manufacturer Part Number: |
| 62618-428 |
| Tempurature Rating: |
| 1200.0 degrees fahrenheit |
| Nut Quantity: |
| 20 |
| Thread Series: |
| Unf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| Between 33.0 rockwell c and 44.0 rockwell c |
| Thread Size: |
| 0.250 inches |
| Material: |
| Steel comp 321 channel |

Silver nut

Surface Treatment:

NSN 5310-00-779-4578

Gang Channel Self-locking Nut Assembly - Page 2 of 2



| Surface | Treatment | Specification: |
|---------|------------------|----------------|
|---------|------------------|----------------|

Ams 2410 assn standard single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0