NSN 5310-00-779-6811

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-779-6811 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 1.292 inches **Nut Height:** 0.281 inches **Plate Thickness:** 0.032 inches Plate Width: Between 0.350 inches and 0.516 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.495 inches and 0.505 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.998 inches and 1.002 inches **Tempurature Rating:** 800.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 28 **Hardness Rating:**

49.0 rockwell c

Thread Size:
0.250 inches

Mounting Hole Countersink Angle:
Between 98.0 degrees and 102.0 degrees

NSN 5310-00-779-6811

Plate Self-locking Nut - Page 2 of 2

Material:



Iron alloy 660
Material Specification:
Ams 5735 assn standard single material response or ams 5737 assn standard single material response or ams 5525 assn standard single
material response
Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2410 assn standard single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0