NSN 5310-00-809-8533

Flat Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-809-8533

Cross Sectional Shape:
Rectangular
Hole Diameter:
Between 0.805 inches and 0.842 inches
Edge Shape:
Round
Center Hole Shape:
1 round
Thickness:
Between 0.108 inches and 0.160 inches
Overall Diameter:
Between 1.462 inches and 1.499 inches
End Application:
W/s: fire pumps; vehicle, aircraft refueler r-14; shipboard material handling equipment (mhe); airborne mobile dir air spt ctl (2id),
(02mjul83)(an/uyq-3a); communications terminal, satellite an/gsc-3 (v)1; support equipment, b-1 aircraft; elevators, aircraft; torpedo, mk
48; stream (std.Tensioned replensihment at sea method); nsn 4210-01-486-1035 tfft (tactical fire fighting truck); 2320-01-097-0248,
2320-01-097-0249, 2320-01-100-7672, 2320-01-097-0260, 2320-01-195-7641 hemtt (heavy expanded mobility tactical trucks);
3990-01-444-6174 bitum distributor; 3990-01-444-5196 cement mixer; and mrap buffalo mk2a2
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Specification Or Standard:
A type and 1 grade and a class
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A022b0