NSN 5310-00-810-3563

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-810-3563

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.656 inches |
| Nut Style: |
| Blind rivet w/smooth round shank |
| Nut Diameter: |
| Between 0.409 inches and 0.413 inches |
| Nut Length: |
| Between 1.203 inches and 1.233 inches |
| Err Default: |
| +0.106/+0.181 inches |
| Shank End Type: |
| Closed |
| Thread Series: |
| Unc |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 0.312 inches |
| Head Countersink Angle: |
| Between 99.00 degrees and 101.00 degrees |
| Material: |
| Aluminum alloy 6053 |
| Material Specification: |
| Qq-a-430, t4 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 2 military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |
| 702100 |
| |

NSN 5310-00-810-3563

Blind Rivet Plain Nut - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

