

View Online at https://aerobasegroup.com/nsn/5310-00-811-9904

| view Online at https://aerobasegroup.com/nsi/3310-00- |
|---|
| Thread Class:   |
| 3b  |
| Thread Direction:                                     |
| Right-hand  |
| Locking Feature:                                      |
| Prevailing torque all metal design                    |
| Washer Outside Diameter:                              |
| 0.791 inches  |
| Lubrication:  |
| Soluble lubricant                                     |
| Overall Height:                                       |
| 0.609 inches  |
| Nut Style:  |
| Double hexagon  |
| Washer Thickness:                                     |
| 0.104 inches  |
| Width Across Flats:                                   |
| Between 0.616 inches and 0.627 inches                 |
| Tempurature Rating:                                   |
| 1200.0 degrees fahrenheit                             |
| Thread Series:  |
| Unjf  |
| Thready Qty Per Inch (tpi):                           |
| 20  |
| Hardness Rating:                                      |
| 36.0 rockwell c                                       |
| Thread Size:  |
| 0.500 inches  |
| Material:   |
| Iron alloy 660  |
| Material Specification:                               |
| Ams 5735 assn standard single material response       |
| Precious Material:                                    |
| Silver  |
| Surface Treatment:                                    |
| Silver  |
| Surface Treatment Specification:                      |
| Ams 2410 assn standard single treatment response      |
| Shelf Life:   |
| N/a   |
| Unit Of Moasuro:                                      |

Unit Of Measure:

---



Demilitarization:

No

Fiig:

A021a0