

View Online at <https://aerobasegroup.com/nsn/5310-00-813-1939>

**Thread Pitch Diameters:**

+5.0219/+5.0278 inches

**Thread Direction:**

Left-hand

**Drive Point Depth:**

0.125 inches

**Nut Style:**

Round

**Nut Diameter:**

5.750 inches

**Nut Thickness:**

0.400 inches

**Drive Point Width:**

0.320 inches

**Drive Point Quantity:**

8

**Hole Type And Quantity:**

9 tapped

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

16

**Hardness Rating:**

Between 27.0 rockwell c and 32.0 rockwell c

**Thread Size:**

5.062 inches

**Hole Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Configuration j

**Countersink Angle:**

90.0 degrees nut

**Hole Thread Diameter:**

0.164 inches

**Product Name:**

Navy special project

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Tin and cadmium

**Surface Treatment Specification:**

Kps 537, cl 1, fscm 84955 mfr ref all treatment responses

**Test Data Document:**

84955-kps208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6758 spec.