

View Online at <https://aerobasegroup.com/nsn/5310-00-820-6653>

**Hole Diameter:**

Between 0.636 inches and 0.653 inches

**Outside Diameter:**

1.079 inches

**Material Thickness:**

Between 0.156 inches and 0.166 inches

**End Application:**

W/s: boilers, 1200 psi; support equipment, b-1 aircraft; elevators, aircraft; vehicle, aircraft refueler r-14; stream (std. Tensioned replenishment at sea method); airborne mobile dir air ctl (2id), (02mjul83)(an/uyq-3a); mtr family (includes tamcns d0198, d1062, d1073, & d1213); fire pumps; I.P. Compressors; communications terminal, satellite an/gsc-3 (v)1; 2320-01-097-0260 hemtt (heavy expanded mobility tactical trucks)

**Hardness Rating:**

Between 45.0 rockwell c and 53.0 rockwell c

**Material:**

Steel comp 1060 or steel comp 1561 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel comp 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1080

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Style Designator:**

Split helical-right hand

**Departure From Cited Designator:**

As modified by surface treatment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0