

View Online at <https://aerobasegroup.com/nsn/5310-00-820-6653>

Hole Diameter:

Between 0.636 inches and 0.653 inches

Outside Diameter:

1.079 inches

Material Thickness:

Between 0.156 inches and 0.166 inches

End Application:

W/s: boilers, 1200 psi; support equipment, b-1 aircraft; elevators, aircraft; vehicle, aircraft refueler r-14; stream (std. Tensioned replenishment at sea method); airborne mobile dir air ctl (2id), (02mjul83)(an/uyq-3a); mtvr family (includes tamcns d0198, d1062, d1073, & d1213); fire pumps; I.P. Compressors; communications terminal, satellite an/gsc-3 (v)1; 2320-01-097-0260 hemtt (heavy expanded mobility tactical trucks)

Hardness Rating:

Between 45.0 rockwell c and 53.0 rockwell c

Material:

Steel comp 1060 or steel comp 1561 or steel comp 1064 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel comp 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1080

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Style Designator:

Split helical-right hand

Departure From Cited Designator:

As modified by surface treatment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0