## NSN 5310-00-820-7155

Clinch Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-820-7155

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque with nonmetallic insert  |
| Pilot Diameter:  |
| Between 0.127 inches and 0.131 inches  |
| Pilot Length:  |
| Between 0.057 inches and 0.063 inches  |
| Counterbore Diameter:  |
| 0.096 inches nut and 0.101 inches nut  |
| Nut Style:   |
| Clinch   |
| Nut Diameter:  |
| Between 0.167 inches and 0.177 inches  |
| Nut Height:  |
| Between 0.122 inches and 0.138 inches  |
| Nut Counterbore Depth:   |
| 0.060 inches nut   |
| Tempurature Rating:  |
| 350.0 degrees fahrenheit   |
| Thread Series:   |
| Unc  |
| Thready Qty Per Inch (tpi):  |
| 56   |
| Thread Size:   |
| 0.086 inches   |
| Material:  |
| Steel comp 1212 nut  |
| Material Specification:  |
| Mil-m-20693 military specification 1st material response locking insert              |
| Surface Treatment:   |
| Cadmium except insert  |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 3 federal specification single treatment response except insert |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

## NSN 5310-00-820-7155

Clinch Self-locking Nut - Page 2 of 2

Fiig: A021a0 Mil-std (military Standard):

Mil-m-20693 spec.

