

View Online at <https://aerobasegroup.com/nsn/5310-00-839-2066>

Thread Class:

2b

Thread Direction:

Right-hand

Nut Style:

Hexagon

Nut Height:

Between 0.301 inches and 0.324 inches

End Application:

W/s: helicopter, advance attack, ah-1w; helicopter, uscg search and rescue, hh-60j; helicopter, search and rescue, hh-60h; radar set, firefinder (an/tpq-36); helicopter, carrier based asw, sh-60f; armored vehicle launch bridge (m60a1 & m48a5); torpedo, adcap 48; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); helicopter, mh-53e; truck, cargo, 5-ton, 6x6, xlwb w/e; artic kit for hemtt family (heavy expanded mobility tactical trucks)

Width Across Flats:

Between 0.861 inches and 0.875 inches

Thread Series:

Unf

Thready Qty Per Inch (tpi):

18

Hardness Rating:

Between 32.0 rockwell b and 90.7 rockwell b

Thread Size:

0.562 inches

Bearing Surface Type:

Chamfered or washer faced

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Specification Or Standard:

2 type and 5 style and b grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0