

View Online at <https://aerobasegroup.com/nsn/5310-00-842-1288>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all nonmetallic design

Counterbore Diameter:

0.245 inches nut

Overall Height:

Between 0.625 inches and 0.645 inches

Mounting Hole Diameter:

Between 0.130 inches and 0.135 inches

Nut Style:

Plate

Nut Length:

0.812 inches

Nut Height:

0.311 inches

Plate Thickness:

Between 0.070 inches and 0.090 inches

Plate Width:

0.572 inches

Nut Counterbore Depth:

0.119 inches nut and 0.139 inches nut

Nut Mounting Provision:

Straight holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.339 inches and 0.349 inches

Center To Center Distance Between Mounting Holes Along Width:

Between 0.298 inches and 0.302 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Hardness Rating:

Between 55.0 shore durometer a and 65.0 shore durometer a

Thread Size:

0.190 inches

Material:

Rubber synthetic nut

Material Specification:

Mil-r-6855 cl1, grade 60 military specification single material response nut

Surface Treatment:

Anodize shell

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response shell

Specification Data:

81205-bacn10en manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-r-6855 spec.