## NSN 5310-00-849-7028

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-849-7028 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Overall Height:** 0.640 inches **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.989 inches **Nut Height:** 0.313 inches **Plate Thickness:** 0.030 inches Plate Width: 0.568 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.686 inches and 0.690 inches **Tempurature Rating:** Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit **Thread Series:** Unjc **Features Provided:** Floating nut Thready Qty Per Inch (tpi):

32 **Hardness Rating:** 60.0 shore durometer a **Thread Size:** 0.164 inches

# NSN 5310-00-849-7028

Plate Self-locking Nut - Page 2 of 2



ate	

Steel washer or aluminum alloy washer

### **Material Specification:**

Mil-r-6855 class 1 grade 60 military specification single material response seal

### **Surface Treatment Specification:**

Qq-p-416 type2, class3 federal specification single treatment response shell

### **Specification Data:**

80205-nas1473 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-r-6855 spec.