# NSN 5310-00-849-8493

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-849-8493 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Counterbore Diameter:** 0.203 inches nut and 0.208 inches nut **Mounting Hole Diameter:** 0.098 mils and 0.103 centimeters **Nut Style:** Plate **Nut Length:** 0.906 inches **Distance From Base To Center Of Aperture:** Between 0.266 inches and 0.296 inches **Nut Height:** 0.343 centimeters **Plate Thickness:** 0.075 centimeters Plate Width: 0.619 inches **Nut Counterbore Depth:** 0.055 inches nut and 0.085 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style: Distance From Mounting Hole Center To Base:** Between 0.469 inches and 0.499 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.248 inches and 0.252 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32

**Thread Size:** 

0.190 inches

# NSN 5310-00-849-8493

Plate Self-locking Nut - Page 2 of 2



ate	

Plastic polyamide locking insert

#### **Surface Treatment:**

Anodize shell or chromate shell or cadmium shell

## **Surface Treatment Specification:**

Mil-a-8625 type 1 military specification 1st treatment response shell or mil-c-5541 military specification 2nd treatment response shell or qq-p-416 federal specification 3rd treatment response shell

## **Specification Data:**

80205-nas1033 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.