

View Online at <https://aerobasegroup.com/nsn/5310-00-856-0587>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Drive Point Depth:

Between 0.110 inches and 0.140 inches

Nut Style:

Round

Nut Diameter:

Between 4.297 inches and 4.317 inches

Nut Thickness:

Between 0.460 inches and 0.490 inches

Drive Point Width:

Between 0.360 inches and 0.390 inches

Undercut Thickness:

Between 0.045 inches and 0.105 inches

Drive Point Quantity:

4

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Uns

Thready Qty Per Inch (tpi):

12

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Thread Size:

3.527 inches

Material:

Steel comp 4130 nut

Material Specification:

Nylon zytel fscm 77272 mfr ref 2nd material response locking insert

Surface Treatment:

Phosphate zinc nut

Surface Treatment Specification:

Mil-p-16232, ty z, cl 4a military specification single treatment response nut

Specification Data:

81205-bacn10gr manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6758 spec.