

View Online at <https://aerobasegroup.com/nsn/5310-00-863-1229>

**Thread Pitch Diameters:**

+2.3239/+2.3290 inches

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Drive Point Depth:**

Between 0.079 inches and 0.109 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 2.923 inches and 2.943 inches

**Nut Thickness:**

Between 0.429 inches and 0.459 inches

**Drive Point Width:**

Between 0.234 inches and 0.266 inches

**Undercut Thickness:**

Between 0.044 inches and 0.106 inches

**Drive Point Quantity:**

4

**Temperature Rating:**

Between -75.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Thread Size:**

2.360 inches

**Countersink Angle:**

90.0 degrees nut and 110.0 degrees nut

**Material:**

Steel comp 4130 nut

**Material Specification:**

Nylon zytel-103 fscm 81205 mfr ref 2nd material response locking insert

**Surface Treatment:**

Phosphate zinc nut

**Surface Treatment Specification:**

Mil-p-16232, ty z, cl 4a military specification single treatment response nut

**Specification Data:**

81205-bacn10gr manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-p-16232 spec.