NSN 5310-00-878-3579

Recessed Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-878-3579

1.375 inches Outside Diameter: Between 2.500 inches and 2.562 inches Recess Diameter: 1.875 inches Material Thickness: 0.625 inches Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material surface Treatment: Cadmium	
Between 2.500 inches and 2.562 inches Recess Diameter: 1.875 inches Material Thickness: 0.625 inches Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material specification:	
Recess Diameter: 1.875 inches Material Thickness: 0.625 inches Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material 5th m	
Material Thickness: 0.625 inches Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material specification:	
Material Thickness: 0.625 inches Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material specification 1st material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 3rd material response or astm a108 assn standard 5th material specification 3rd material response or astm a108 assn standard 5th material specification 3rd material response or astm a108 assn standard 5th material specification 3rd material response or astm a108 assn standard 5th material specification 3rd material response or astm a108 assn standard 5th material specification 3rd material specification 3rd material response or astm a108 assn standard 5th material specification 3rd material spe	
Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material respons	
Material: Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material response	
Steel comp a or steel comp b or steel comp c or steel comp 1008 or steel comp 1025 Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material specification 2nd material response or astm a108 assn standard 5th material specification 2nd material specification 2	
Material Specification: Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal specification 3nd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material response or qq-s-741 federal specification 2nd material response or qq-s-741 federal sp	
Qq-s-741 federal specification 1st material response or qq-s-741 federal specification 2nd qq-s-741 federal specif	
specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material response o	
Surface Treatment:	
	erial respons
Cadmium	
Oddinan	
Surface Treatment Specification:	
Qq-p-416, type 2, cl 2 federal specification single treatment response	
Style Designator:	
15 recessed	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A022b0	