

View Online at <https://aerobasegroup.com/nsn/5310-00-893-6108>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Mounting Hole Diameter:

Between 0.130 inches and 0.135 inches

Nut Style:

Plate

Nut Length:

Between 0.875 inches and 0.905 inches

Distance From Base To Center Of Aperture:

Between 0.266 inches and 0.296 inches

Nut Height:

Between 0.313 inches and 0.343 inches

Plate Thickness:

Between 0.035 inches and 0.065 inches

Plate Width:

Between 0.491 inches and 0.521 inches

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Mounting Hole Center To Base:

0.500 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.248 inches and 0.252 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unc

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Material:

Plastic polyamide locking insert

Material Specification:

Mil-p-17091, type 1 military specification single material response locking insert

Surface Treatment:

Anodize shell

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-p-17091 spec.