## NSN 5310-00-893-6108

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-893-6108 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque with nonmetallic insert **Mounting Hole Diameter:** Between 0.130 inches and 0.135 inches **Nut Style:** Plate **Nut Length:** Between 0.875 inches and 0.905 inches **Distance From Base To Center Of Aperture:** Between 0.266 inches and 0.296 inches **Nut Height:** Between 0.313 inches and 0.343 inches **Plate Thickness:** Between 0.035 inches and 0.065 inches Plate Width: Between 0.491 inches and 0.521 inches **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Mounting Hole Center To Base:** 0.500 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.248 inches and 0.252 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unc **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches

Material:

Plastic polyamide locking insert

**Material Specification:** 

Mil-p-17091, type 1 military specification single material response locking insert

## NSN 5310-00-893-6108

Plate Self-locking Nut - Page 2 of 2



Surface Treatment:
Anodize shell
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response shell
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0

Mil-p-17091 spec.

Mil-std (military Standard):