NSN 5310-00-895-6233

Barrel Self-locking Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-895-6233

Thread Class: 3b Thread Direction: Right-hand Locking Feature: Prevailing torque with nonmetallic insert Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life: N/a
Thread Direction: Right-hand Locking Feature: Prevailing torque with nonmetallic insert Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Right-hand Locking Feature: Prevailing torque with nonmetallic insert Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Locking Feature: Prevailing torque with nonmetallic insert Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Prevailing torque with nonmetallic insert Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Tempurature Rating: 250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
250.0 degrees fahrenheit Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Thread Series: Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Unf Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Thready Qty Per Inch (tpi): 24 Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Thread Size: 0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
0.312 inches Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Surface Treatment: Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Cadmium nut Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Qq-p-416, type 2, cl 3 federal specification single treatment response nut Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A021a0