

View Online at <https://aerobasegroup.com/nsn/5310-00-900-3368>

**Hole Diameter:**

Between 0.505 inches and 0.510 inches

**Outside Diameter:**

Between 1.240 inches and 1.260 inches

**Material Thickness:**

Between 0.177 inches and 0.180 inches

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

Between 34.0 rockwell c and 38.0 rockwell c

**Top Recess Diameter:**

Between 0.604 inches and 0.620 inches

**Bottom Recess Angle:**

90.0 degrees

**Top Recess Angle:**

90.0 degrees

**Criticality Code Justification:**

Feat

**Bottom Recess Diameter:**

Between 0.604 inches and 0.620 inches

**Surface Finish:**

100.0 microinches all surfaces

**Special Features:**

Extreme outer edges of both bearing surfaces rounded

**Material:**

Steel

**Material Specification:**

Mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Style Designator:**

Recessed both sides

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A022b0

**Mil-std (military Standard):**

Mil-s-5000 spec.