## NSN 5310-00-901-0032

Round Plain Nut - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5310-00-901-0032  |  |
|--|--|
| Thread Class:  |  |
| 3b   |  |
| Thread Direction:  |  |
| Right-hand   |  |
| Drive Point Depth:   |  |
| Between 0.080 inches and 0.100 inches  |  |
| Nut Style:   |  |
| Round  |  |
| Nut Diameter:  |  |
| Between 2.890 inches and 2.910 inches  |  |
| Nut Thickness:   |  |
| Between 0.302 inches and 0.322 inches  |  |
| Drive Point Width:   |  |
| 0.190 mils and 0.210 centimeters   |  |
| Drive Point Quantity:  |  |
| 4  |  |
| Drilled Hole Diameter:   |  |
| 0.052 inches   |  |
| Hole Type And Quantity:  |  |
| 2 drilled  |  |
| Thread Series:   |  |
| Un   |  |
| Thready Qty Per Inch (tpi):  |  |
| 16   |  |
| Thread Size:   |  |
| 2.500 inches   |  |
| Hole Configuration Style:  |  |
| Configuration g  |  |
| Material:  |  |
| Aluminum alloy   |  |
| Material Specification:  |  |
| Qq-a-200/2, comp 2014, t6 federal specification 1st material response or qq-a-200/3, comp 2024, t4 federal specification 2nd material    |  |
| response or qq-a-225/4, comp 2014, t6 federal specification 3rd material response or qq-a-225/6, comp 2024, t4 federal specification 4th |  |
| material response  |  |
| Surface Treatment:   |  |
| Anodize  |  |
| Surface Treatment Specification:   |  |
| Mil-a-8625, type 1 military specification single treatment response  |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
| <del></del>  |  |
|  |  |

No

Demilitarization:

## NSN 5310-00-901-0032

Round Plain Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.