NSN 5310-00-901-0032

Round Plain Nut - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5310-00-901-0032 | |
|--|--|
| Thread Class: | |
| 3b | |
| Thread Direction: | |
| Right-hand | |
| Drive Point Depth: | |
| Between 0.080 inches and 0.100 inches | |
| Nut Style: | |
| Round | |
| Nut Diameter: | |
| Between 2.890 inches and 2.910 inches | |
| Nut Thickness: | |
| Between 0.302 inches and 0.322 inches | |
| Drive Point Width: | |
| 0.190 mils and 0.210 centimeters | |
| Drive Point Quantity: | |
| 4 | |
| Drilled Hole Diameter: | |
| 0.052 inches | |
| Hole Type And Quantity: | |
| 2 drilled | |
| Thread Series: | |
| Un | |
| Thready Qty Per Inch (tpi): | |
| 16 | |
| Thread Size: | |
| 2.500 inches | |
| Hole Configuration Style: | |
| Configuration g | |
| Material: | |
| Aluminum alloy | |
| Material Specification: | |
| Qq-a-200/2, comp 2014, t6 federal specification 1st material response or qq-a-200/3, comp 2024, t4 federal specification 2nd material | |
| response or qq-a-225/4, comp 2014, t6 federal specification 3rd material response or qq-a-225/6, comp 2024, t4 federal specification 4th | |
| material response | |
| Surface Treatment: | |
| Anodize | |
| Surface Treatment Specification: | |
| Mil-a-8625, type 1 military specification single treatment response | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| | |

No

Demilitarization:

NSN 5310-00-901-0032

Round Plain Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.