## NSN 5310-00-903-6063

Sleeve Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-903-6063

| Thread Class:   |
|---|
| 2b  |
| Thread Direction:   |
| Right-hand  |
| Counterbore Diameter:   |
| 0.156 inches nut  |
| Nut Style:  |
| Sleeve  |
| Nut Diameter:   |
| 0.250 inches  |
| Nut Length:   |
| 0.220 inches  |
| Boss Diameter:  |
| Between 0.218 inches and 0.219 inches                         |
| Boss Thickness:   |
| 0.080 inches  |
| Nut Counterbore Depth:  |
| 0.188 inches nut and 0.198 inches nut                         |
| Cross-sectional Shape:  |
| Round nut   |
| Tempurature Rating:   |
| Not rated   |
| Thread Series:  |
| Unc   |
| Thready Qty Per Inch (tpi):                                   |
| 32  |
| Hardness Rating:  |
| Not rated   |
| Thread Size:  |
| 0.138 inches  |
| Countersink Angle:  |
| 100.0 degrees nut   |
| Material:   |
| Aluminum alloy 6061   |
| Material Specification:                                       |
| Qq-a-225/8, t6 federal specification single material response |
| Surface Treatment:  |
| Chromate  |
| Surface Treatment Specification:                              |
| Mil-c-5541 military specification single treatment response   |
| Shelf Life:   |
| N/a   |

N/a

## NSN 5310-00-903-6063

Sleeve Nut - Page 2 of 2



|    | • • |    |    |    |     |     |    |
|----|-----|----|----|----|-----|-----|----|
| ın | 1+  | Of | ΝЛ | ດລ | CI. | ırı | ο. |
|    |     |    |    |    |     |     |    |

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-c-5541 spec.