

View Online at <https://aerobasegroup.com/nsn/5310-00-912-0658>

Thread Class:

3b

Thread Direction:

Right-hand

Counterbore Diameter:

5.277 inches and 5.283 inches base

Drive Point Depth:

Between 0.170 inches and 0.190 inches

Nut Style:

Round

Nut Diameter:

Between 5.572 inches and 5.576 inches

Nut Thickness:

Between 1.640 inches and 1.660 inches

Drive Point Width:

Between 0.490 inches and 0.510 inches

Drive Point Quantity:

10

Nut Counterbore Depth:

0.110 inches and 0.130 inches base

Hole Type And Quantity:

18 tapped

Thread Series:

Unjs

Thready Qty Per Inch (tpi):

16

Hardness Rating:

Between 32.0 rockwell c and 38.0 rockwell c

Thread Size:

4.9375 inches

Hole Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Configuration f

Countersink Angle:

2.0 degrees and 4.0 degrees base

Hole Thread Diameter:

0.216 inches

Special Features:

54 holes, 0.084 in. Min 0.094 in. Maximum dia, from base to bottom of inside groove beyond threads; inside diameter 4.960 in. Min, 4.970 in. Max, unthreaded portion; external groove, 0.050 in. Min, 0.070 in. Maximum w; 5.390 in. Min, 5.410 in. Maximum od, drive side, at end of chamfer; 10 drive slots, 0.490 in. Min, 0.510 in. Maximum w; radial holes ctr 0.275 in. Fm base; longitudinal holes in groups of three

Material:

Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response or am 6323 assn standard single material response

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2210 assn standard single treatment response or ams 2212 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0