## NSN 5310-00-915-2459



Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-00-915-2459 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Diameter:** Between 0.970 inches and 1.062 inches **Head Height:** 0.044 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.518 inches and 0.522 inches **Head Minor Diameter:** Between 0.444 inches and 0.448 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.394 inches and 0.396 inches **Nut Length:** Between 1.168 inches and 1.198 inches **Nut Grip Range:** +0.130/+0.190 inches **Shank End Type:** Open **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unf

Thready Qty Per Inch (tpi):

24

**Thread Size:** 

0.312 inches

**Head Major Countersink Angle:** 

Between 75.45 degrees and 76.15 degrees

**Countersink Angle:** 

60.0 degrees nut

**Head Minor Countersink Angle:** 

Between 59.45 degrees and 60.15 degrees

## NSN 5310-00-915-2459

**Fiig:** A021a0

Blind Rivet Self-locking Nut - Page 2 of 2



Material:
Steel comp 304 or steel comp 305
Material Specification:
Qq-s-763, cond a federal specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, ty2, class 3 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No