

View Online at <https://aerobasegroup.com/nsn/5310-00-919-0599>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Counterbore Diameter:**

1.330 inches second end and 1.340 inches second end

**Drive Point Depth:**

0.125 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 1.500 inches and 1.520 inches

**Nut Thickness:**

Between 0.330 inches and 0.335 inches

**Drive Point Width:**

Between 0.120 inches and 0.130 inches

**Drive Point Quantity:**

15

**Nut Counterbore Depth:**

0.135 inches second end

**Thread Series:**

Unef

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

Between 32.0 rockwell c and 36.0 rockwell c

**Thread Size:**

0.9375 inches

**Countersink Angle:**

118.0 degrees both ends and 122.0 degrees both ends

**Bearing Surface Finish:**

32.0 microinches

**Special Features:**

Inside groove, 1.391 in. Min, 1.399 in. Maximum id, cbore end

**Material:**

Steel comp 4140

**Material Specification:**

Ams 6381 assn standard single material response or ams 6382 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Ams 2485 assn standard single treatment response

**Test Data Document:**

99207--3-te2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0