

View Online at <https://aerobasegroup.com/nsn/5310-00-926-1835>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Lubrication:**

Soluble lubricant

**Nut Style:**

Hexagon

**Nut Height:**

0.188 inches

**End Application:**

Communications terminal, satellite an/gsc-3 (v)1; aircraft (ac-130h, mc-130h, ec-130e, hc-130); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); radar set, an/tpn-18; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a) ; trainer, b-1b aircraft; support equipment, b-52 aircraft; support equipment, b-1 aircraft; communications terminal, an/ugc-74; ok-520/sqq common winch

**Width Across Flats:**

Between 0.367 inches and 0.376 inches

**Temperature Rating:**

250.0 degrees fahrenheit

**Thread Series:**

Unjf

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Countersink Angle:**

88.0 degrees nut

**Bearing Surface Type:**

Chamfered or washer faced

**Bearing Surface Finish:**

125.0 microinches

**Material:**

Stainless steel nut

**Surface Treatment:**

Passivate except insert

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response except insert

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0