

View Online at <https://aerobasegroup.com/nsn/5310-00-926-1835>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Lubrication:

Soluble lubricant

Nut Style:

Hexagon

Nut Height:

0.188 inches

End Application:

Communications terminal, satellite an/gsc-3 (v)1; aircraft (ac-130h, mc-130h, ec-130e, hc-130); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); radar set, an/tpn-18; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a) ; trainer, b-1b aircraft; support equipment, b-52 aircraft; support equipment, b-1 aircraft; communications terminal, an/ugc-74; ok-520/sqq common winch

Width Across Flats:

Between 0.367 inches and 0.376 inches

Temperature Rating:

250.0 degrees fahrenheit

Thread Series:

Unjf

Thread Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Countersink Angle:

88.0 degrees nut

Bearing Surface Type:

Chamfered or washer faced

Bearing Surface Finish:

125.0 microinches

Material:

Stainless steel nut

Surface Treatment:

Passivate except insert

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0