

View Online at <https://aerobasegroup.com/nsn/5310-00-926-1851>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Lubrication:**

Dry film lubricant

**Nut Style:**

Hexagon

**Nut Height:**

0.282 inches

**End Application:**

Aircraft (ac-130h, mc-130h, ec-130e, hc-130); ticonderoga class cg (47); helicopter observation (ahip), oh-58d; f-22 raptor air dominance fighter; deck machinery; guided missile, intercept; aircraft black hawk (mh-60k special operations aircraft); torpedo, adcap 48; aircraft mh-47e special operations aircraft; surface minesweeping systems; ah-64-d longbow

**Width Across Flats:**

Between 0.553 inches and 0.564 inches

**Temperature Rating:**

250.0 degrees fahrenheit

**Thread Series:**

Unjf

**Thread Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

88.0 degrees nut

**Bearing Surface Type:**

Chamfered or washer faced

**Bearing Surface Finish:**

125.0 microinches

**Material:**

Plastic polyamide locking insert

**Surface Treatment:**

Anodize except insert or chromate except insert

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response except insert or mil-c-5541 military specification 2nd treatment response except insert

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-a-8625 spec.