NSN 5310-00-926-5918

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-926-5918 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.984 inches **Nut Height:** 0.312 inches **Plate Thickness:** 0.075 inches Plate Width: 0.416 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** 0.344 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.686 inches and 0.690 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches

Countersink Angle: 120.0 degrees nut

NSN 5310-00-926-5918

Plate Self-locking Nut - Page 2 of 2

Fiig: A021a0



| Mounting Hole Countersink Angle: |
|---|
| Between 98.0 degrees and 102.0 degrees |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 1 federal specification 1st treatment response or qq-p-416, type 2, class 2 federal specification 2nd treatment |
| response or qq-p-416, type 2, class 3 federal specification 3rd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |