

View Online at <https://aerobasegroup.com/nsn/5310-00-935-1235>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Small End Diameter:**

Between 1.828 inches and 1.860 inches

**Drive Point Depth:**

Between 0.079 inches and 0.109 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 2.089 inches and 2.099 inches

**Nut Thickness:**

Between 0.366 inches and 0.396 inches

**Drive Point Width:**

Between 0.234 inches and 0.266 inches

**Undercut Thickness:**

Between 0.044 inches and 0.106 inches

**Drive Point Quantity:**

4

**Temperature Rating:**

Between -75.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Thread Series:**

Unef

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.5625 inches

**Countersink Angle:**

90.0 degrees nut and 110.0 degrees nut

**Product Name:**

Navy special project

**Material:**

Steel comp 4130 nut

**Material Specification:**

Mil-s-6758, cond f military specification 1st material response nut

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Mil-p-16232, ty z, cl 4a military specification 2nd treatment response

**Specification Data:**

81205-bacn10gr manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6758 spec.