

View Online at https://aerobasegroup.com/nsn/5310-00-939-0960

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque all metal design   |
| Counterbore Diameter:  |
| 0.194 inches nut   |
| Overall Length:  |
| 72.000 inches  |
| Overall Width:   |
| 0.416 inches   |
| Nut Style:   |
| Gang channel, self locking   |
| Channel Style:   |
| Straight type  |
| Assemblyheight:  |
| 0.250 inches   |
| Channel Height:  |
| 0.250 inches   |
| Nut Spacing:   |
| Between 0.990 inches and 1.010 inches  |
| Nut Counterbore Depth:   |
| 0.062 inches nut   |
| Tempurature Rating:  |
| 800.0 degrees fahrenheit   |
| Nut Quantity:  |
| 72   |
| Thread Series:   |
| Unjf   |
| Features Provided:   |
| Floating nut   |
| Thready Qty Per Inch (tpi):  |
|  |
| Thread Size:   |
| 0.190 inches   |
| Material:  |
| Iron alloy 660 nut   |
| Material Specification:  |
| Ams 5525 assn standard single material response nut or ams 5732 assn standard single material response nut or ams 5737 assn standard |

single material response nut

## **Precious Material And Location:**

Nut silver

## NSN 5310-00-939-0960

Gang Channel Self-locking Nut Assembly - Page 2 of 2



**Precious Material:** 

Silver

Surface Treatment:

Passivate channel

Surface Treatment Specification:

Ams 2410 assn standard single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0