## NSN 5310-00-944-5981

Plate Nut Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-00-944-5981

Mounting Hole Diameter:
Between 0.102 inches and 0.108 inches
Nut Style:
Plate nut spacer
Nut Length:
Between 1.063 inches and 1.093 inches
Thru-hole Diameter:
Between 0.210 inches and 0.220 inches
Plate Thickness:
Between 0.075 inches and 0.105 inches
Plate Width:
0.500 inches
Nut Mounting Provision:
Countersunk holes
Mounting Provision Location:
Nut projection side
Mounting Hole Arrangement Style:
2 holes
Distance From Aperture Center To Mounting Hole Center:
Between 0.341 inches and 0.347 inches
· · · · · · · · · · · · · · · · · · ·
Between 0.341 inches and 0.347 inches
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:  Aluminum alloy
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:  Aluminum alloy  Shelf Life:
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:  Aluminum alloy  Shelf Life:  N/a
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:  Aluminum alloy  Shelf Life:  N/a
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:  Aluminum alloy  Shelf Life:  N/a  Unit Of Measure:
Between 0.341 inches and 0.347 inches  Center To Center Distance Between Mounting Holes Along Length:  Between 0.310 inches and 0.314 inches  Mounting Hole Countersink Angle:  100.0 degrees  Special Features:  Aluminum cladding  Material:  Aluminum alloy  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: