

View Online at <https://aerobasegroup.com/nsn/5310-00-956-3660>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Counterbore Diameter:**

0.254 inches boss and 0.260 inches boss

**Flange Diameter:**

Between 1.240 inches and 1.280 inches

**Flange Thickness:**

Between 0.183 inches and 0.191 inches

**Nut Style:**

Sleeve

**Nut Diameter:**

Between 0.911 inches and 0.912 inches

**Nut Length:**

Between 0.587 inches and 0.609 inches

**Nut Counterbore Depth:**

0.150 inches boss and 0.170 inches boss

**Drilled Hole Diameter:**

0.055 inches

**Hole Type And Quantity:**

3 drilled

**Cross-sectional Shape:**

Round

**Thread Series:**

Unf

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Hole Configuration Style:**

Configuration g

**Special Features:**

Three through holes, 150 inch dia., equally spaced on same bolt circle; sleeve stepped segment 0.911 to 0.912 incheo.D. And 0.137 to 0.139 inche deep

**Material:**

Steel

**Material Specification:**

Ams5645 assn standard single material response

**Precious Material And Location:**

Threads silver

**Surface Treatment:**

Silver threads

**Surface Treatment Specification:**

Ams2410 assn standard single treatment response threads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0