## NSN 5310-00-956-3660



Sleeve Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-00-956-3660 **Thread Class:** 3b **Thread Direction:** Right-hand **Counterbore Diameter:** 0.254 inches boss and 0.260 inches boss Flange Diameter: Between 1.240 inches and 1.280 inches Flange Thickness: Between 0.183 inches and 0.191 inches **Nut Style:** Sleeve **Nut Diameter:** Between 0.911 inches and 0.912 inches **Nut Length:** Between 0.587 inches and 0.609 inches **Nut Counterbore Depth:** 0.150 inches boss and 0.170 inches boss **Drilled Hole Diameter:** 0.055 inches **Hole Type And Quantity:** 3 drilled **Cross-sectional Shape:** Round **Thread Series:** Unf Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Hole Configuration Style:** Configuration g **Special Features:** Three through holes, 150 inch dia., equally spaced on same bolt circle; sleeve stepped segment 0.911 to 0.912 incheo.D. And 0.137 to 0.139 inche deep Material: Steel

**Material Specification:** 

Ams5645 assn standard single material response

**Precious Material And Location:** 

Threads silver

**Surface Treatment:** 

Silver threads

## NSN 5310-00-956-3660

Sleeve Nut - Page 2 of 2



Ams2410 assn standard single treatment response threads

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0