NSN 5310-00-956-4838

Key Washer - Page 1 of 1



ului
View Online at https://aerobasegroup.com/nsn/5310-00-956-4838
Hole Diameter:
Between 4.801 inches and 4.831 inches
Outside Diameter:
Between 5.688 inches and 5.733 inches
Internal Prebent Key Length:
Between 0.250 inches and 0.312 inches
External Prebent Key Width:
Between 0.360 inches and 0.390 inches
Internal Prebent Key Width:
Between 0.313 inches and 0.353 inches
Overall Distance Including Keys:
6.469 inches
External Key Quantity:
19
Material Thickness:
Between 0.118 inches and 0.132 inches
Material:
Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 101
or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp
1030 or steel comp 1035 or steel comp 1023 or steel comp 1524 or steel comp 1025
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium and chromate or zinc and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification 1st treatment response or astm b633, type 2, class 3 assn standard 2nd treatment response
Style Designator:
Key
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A022b0