Barrel Self-locking Nut - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5310-00-957-3717



| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Non-floating self-locking barrel |
| Nut Diameter: |
| Between 0.866 inches and 0.869 inches |
| Nut Length: |
| Between 0.844 inches and 0.874 inches |
| Nut Height: |
| Between 0.685 inches and 0.715 inches |
| Tempurature Rating: |
| 450.0 degrees fahrenheit |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 20 |
| 20 Hardness Rating: |
| Between 25.0 rockwell c and 35.0 rockwell c |
| Thread Size: |
| 0.500 inches |
| Material: |
| |
| Steel comp 4130 Material Specification: |
| Aisi assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A021a0 |
| |