

View Online at https://aerobasegroup.com/nsn/5310-00-958-8845

| iew Online at https://aerobasegroup.com/nsh/5310-00-958-8845  |
|---|
| hread Class:  |
| b   |
| hread Direction:  |
| light-hand  |
| ocking Feature:   |
| Prevailing torque all metal design  |
| Vasher Outside Diameter:  |
| .660 inches   |
| counterbore Diameter:   |
| .407 inches nut and 0.417 inches nut  |
| Overall Height:   |
| etween 0.341 inches and 0.361 inches  |
| lut Style:  |
| lat with turned up edge   |
| lut Height:   |
| .188 inches   |
| lut Counterbore Depth:  |
| .072 inches nut and 0.087 inches nut  |
| Vidth Across Flats:   |
| etween 0.430 inches and 0.439 inches  |
| hread Series:   |
| Injf  |
| hready Qty Per Inch (tpi):  |
| 4   |
| lardness Rating:  |
| etween 36.0 rockwell c and 40.0 rockwell c  |
| hread Size:   |
| .375 inches   |
| laterial:   |
| teel comp e4340 nut or steel comp 4340 nut or steel comp 8740 nut   |
| laterial Specification:   |
| Ail-s-5000 military specification 1st material response nut or mil-s-5000 military specification 2nd material response nut or mil-s-6049 milita |
| pecification 3rd material response nut  |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 3 federal specification single treatment response  |
| helf Life:  |
| l/a   |
| Init Of Measure:  |
|   |
| Demilitarization:   |
| lo  |
|   |

Assembled Washer Self-locking Nut - Page 2 of 2



Fiig: A021a0

Mil-std (military Standard):

Mil-s-5000 spec.