NSN 5310-00-974-9781

Round Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-00-974-9781

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design or prevailing torque with nonmetallic insert |
| Small End Diameter: |
| 1.291 inches |
| Drive Point Depth: |
| Between 0.084 inches and 0.104 inches |
| Nut Style: |
| Round |
| Nut Diameter: |
| 1.572 inches |
| Nut Thickness: |
| 0.463 inches |
| Drive Point Width: |
| Between 0.178 inches and 0.198 inches |
| Undercut Thickness: |
| 0.104 inches |
| Drive Point Quantity: |
| 4 |
| Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit |
| Thread Series: |
| Uns |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.968 inches |
| Material: |
| Steel comp 1018 |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Phosphate |
| Special Test Features: |
| Humidity test time reduced to 120hours |
| Test Data Document: |
| 81349-e5272 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 5310-00-974-9781

Round Self-locking Nut - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A021a0