

View Online at <https://aerobasegroup.com/nsn/5310-00-974-9785>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design or prevailing torque with nonmetallic insert

**Small End Diameter:**

2.010 inches

**Drive Point Depth:**

Between 0.084 inches and 0.104 inches

**Nut Style:**

Round

**Nut Diameter:**

2.260 inches

**Nut Thickness:**

0.510 inches

**Drive Point Width:**

Between 0.240 inches and 0.260 inches

**Undercut Thickness:**

0.104 inches

**Drive Point Quantity:**

4

**Temperature Rating:**

Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit

**Thread Series:**

Uns

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.562 inches

**Material:**

Steel comp 1018

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Phosphate

**Special Test Features:**

Humidity test time reduced to 120hours

**Test Data Document:**

81349-e5272 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0