NSN 5310-01-006-9010

Plate Nut Spacer - Page 1 of 1

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5310-01-006-9010

Between 0.458 inches and 0.468 inches Plate Thickness: 0.090 inches Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Materials Aluminum alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h34 federal specification 3rd material response or qq-a-250/8, h34 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mill-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A021a0	
Plate nu spacer Nurt Longth: 1.125 inches Thru-hole Diameter: Between 0.458 inches and 0.468 inches Plate Thickness: 0.090 inches Nurt Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Mounting Hole Arrangement Style: 2 holes Product Name: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material: Aluminum alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: Na Unit Of Measure: — Demilitarization: No Fig: A021a0	Mounting Hole Diameter:
Plate nut spacer Nut Length: 1.125 inches 1.175 inches 1.	Between 0.158 inches and 0.164 inches
Nut Length: 1.125 inches 1.125	Nut Style:
1.125 inches Thru-hole Diameter: Between 0.458 inches and 0.468 inches Plate Thickness: 0.090 inches Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mill-a-8625, type 2 military specification single treatment response Specification Data: S00205-nas463 professional/industrial association standard Shoft Life: N/a Unit Of Measure: Demilitarization: No Filig: A021a0	Plate nut spacer
Thru-hole Diameter: Between 0.458 inches and 0.468 inches Piate Thickness: 0.090 inches Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Sheft Life: N/a Unit Of Measure: Demilitarization: No Filig: A021a0	Nut Length:
Thrushole Diameter: Between 0.458 inches and 0.468 inches Plate Thickness: 0.090 inches Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material: Aluminum alloy 5052, imper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response Surface Treatment Specification 2nd material response Surface Treatment Specification 2nd material response or qq-a-250/8, h34 federal specification 2nd mat	1.125 inches
Plate Thickness: 0.090 inches Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h34 federal specification 3rd material response or qq-a-250/8, h34 federal specification 3rd material response or qq-a-250/8, h39 federal specification 3rd material response or qq-a-250/8, h34 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mill-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A021a0	Thru-hole Diameter:
Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A021a0	Between 0.458 inches and 0.468 inches
Nut Mounting Provision: Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Plate Thickness:
Straight holes Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	0.090 inches
Mounting Hole Arrangement Style: 2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Nut Mounting Provision:
2 holes Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A021a0	Straight holes
Distance From Aperture Center To Mounting Hole Center: Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mila-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A021a0	Mounting Hole Arrangement Style:
Between 0.559 inches and 0.565 inches Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A021a0	2 holes
Product Name: Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Distance From Aperture Center To Mounting Hole Center:
Navy special project Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Between 0.559 inches and 0.565 inches
Special Features: Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A021a0	Product Name:
Dyed orange Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A021a0	Navy special project
Material: Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Special Features:
Aluminum alloy 5052 Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Dyed orange
Material Specification: Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Material:
Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Aluminum alloy 5052
response or qq-a-250/8, h36 federal specification 3rd material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Material Specification:
Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Qq-a-250/8, alloy 5052, temper h32 federal specification 1st material response or qq-a-250/8, h34 federal specification 2nd material
Anodize Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	response or qq-a-250/8, h36 federal specification 3rd material response
Surface Treatment Specification: Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Surface Treatment:
Mil-a-8625, type 2 military specification single treatment response Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Anodize
Specification Data: 80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Surface Treatment Specification:
80205-nas463 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Mil-a-8625, type 2 military specification single treatment response
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig: A021a0	80205-nas463 professional/industrial association standard
Unit Of Measure: Demilitarization: No Fiig: A021a0	Shelf Life:
Demilitarization: No Fiig: A021a0	N/a
No Fiig: A021a0	Unit Of Measure:
No Fiig: A021a0	
Fiig: A021a0	Demilitarization:
A021a0	No
	Fiig:
Mil-std (military Standard):	A021a0
	Mil-std (military Standard):