## NSN 5310-01-012-1612

Blind Rivet Plain Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-012-1612

| Thread Class:   |
|---|
| 3b  |
| Thread Direction:   |
| Right-hand  |
| Head Style:   |
| Flat keyed  |
| Head Diameter:  |
| Between 0.766 inches and 0.796 inches                               |
|   |
| Key Length: 0.128 inches  |
| Head Height:  |
| 0.088 inches  |
|   |
| Nut Style:  |
| Blind rivet w/smooth round shank                                    |
| Nut Diameter:   |
| Between 0.486 inches and 0.490 inches                               |
| Nut Length:   |
| Between 0.829 inches and 0.859 inches                               |
| Err Default:  |
| +0.030/+0.115 inches  |
| Shank End Type:   |
| Open  |
| Thread Series:  |
| Unc   |
| Thready Qty Per Inch (tpi):   |
| 16  |
| Thread Size:  |
| 0.375 inches  |
| Material:   |
| Aluminum alloy 6053   |
| Material Specification:   |
| Qq-a-430 federal specification single material response             |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:                                    |
| Mil-a-8625, type 2 military specification single treatment response |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5310-01-012-1612

Blind Rivet Plain Nut - Page 2 of 2



Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.