

View Online at https://aerobasegroup.com/nsn/5310-01-013-3710

| Thread Class: |
|---|
| 3b |
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque all metal design |
| Counterbore Diameter: |
| 0.194 inches nut |
| Lubrication: |
| Dry film lubricant |
| Overall Length: |
| 72.000 inches |
| Overall Width: |
| 0.452 inches |
| Nut Style: |
| Gang channel, self locking |
| Removable Nut Manufacturer Code: |
| 72962 |
| Channel Style: |
| Straight type |
| Assemblyheight: |
| 0.558 inches |
| Channel Height: |
| 0.250 inches |
| Nut Spacing: |
| 0.750 inches |
| Nut Counterbore Depth: |
| 0.375 inches nut |
| Removable Nut Manufacturer Part Number: |
| G18421l6-3 |
| Nut Quantity: |
| 96 |
| Thread Series: |
| Unjf |
| Features Provided: |
| Floating nut |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.190 inches |
| Special Features: |
| Color blue federal standard 595 no. 15526 |

NSN 5310-01-013-3710

Gang Channel Self-locking Nut Assembly - Page 2 of 2



Material:

Iron alloy 660 nut

Material Specification:

Ams5525 assn standard single material response nut

Surface Treatment:

Passivate channel and paint lusterless channel

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response channel and mil-p-85582, type 1, cl 2 military specification 2nd treatment response channel

Specification Data:

76301-st3-463 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-p-85582 spec.