

View Online at <https://aerobasegroup.com/nsn/5310-01-013-9432>

Thread Pitch Diameters:

+0.2467/+0.2473 inches

Thread Direction:

Right-hand

Nut Style:

Hexagon

Nut Height:

Between 0.183 inches and 0.193 inches

Drilled Hole Diameter:

0.046 inches

Hole Type And Quantity:

3 drilled

Width Across Flats:

Between 0.423 inches and 0.437 inches

Thread Series:

Uns

Thready Qty Per Inch (tpi):

48

Thread Size:

0.250 inches

Hole Configuration Style:

Configuration b

Bearing Surface Type:

Chamfered or washer faced

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303s or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 302b or steel comp 384 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446 or steel comp 430f

Material Specification:

66 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Or Standard:

2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No