

View Online at <https://aerobasegroup.com/nsn/5310-01-015-8792>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Pilot Diameter:**

Between 0.158 inches and 0.162 inches

**Pilot Length:**

Between 0.057 inches and 0.063 inches

**Lubrication:**

Dry film lubricant

**Nut Style:**

Clinch

**Nut Diameter:**

Between 0.193 inches and 0.213 inches

**Nut Height:**

Between 0.159 inches and 0.185 inches

**Tempurature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unc

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303s or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

**Material Specification:**

Fed standard 66 federal standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0