NSN 5310-01-022-9002

Plate Self-locking Nut - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5310-01-022-9002



3b **Thread Direction: Right-hand** Locking Feature: Prevailing torque with nonmetallic insert Mounting Hole Diameter: Between 0.098 inches and 0.103 inches Nut Style: Plate Nut Length: 0.984 inches Nut Height: 0.312 inches **Plate Thickness:** 0.075 inches Plate Width: 0.416 inches **Nut Mounting Provision:** Countersunk holes **Mounting Provision Location:** Opposite nut projection side Mounting Hole Arrangement Style: 2 holes **Distance From Aperture Center To Mounting Hole Center:** 0.344 inches Center To Center Distance Between Mounting Holes Along Length: Between 0.686 inches and 0.690 inches **Tempurature Rating:** 250.0 degrees fahrenheit **Thread Series:** Unif **Features Provided:** Floating nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Mounting Hole Countersink Angle:** 100.0 degrees Material: Plastic polyamide locking insert

NSN 5310-01-022-9002

Plate Self-locking Nut - Page 2 of 2



Surface Treatment:

Anodize except insert or chromate except insert

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response except insert or mil-c-5541 military specification 2nd treatment response except insert

insen

Specification Data:

80205-nas1031 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.