
Plate Self-locking Nut - Page 1 of 2





Thread Class: 3b Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.940 inches

Nut Height:

0.328 inches

Plate Thickness:

Between 0.020 inches and 0.030 inches

Plate Width:

0.500 inches

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.339 inches and 0.349 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.686 inches and 0.690 inches

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Color yellow

Material:

Stainless steel

Material Specification:

Ams 5525 assn standard single material response or ams5735 assn standard single material response

NSN 5310-01-027-4677

Plate Self-locking Nut - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

S-p-416, type 1, class 3 federal specification 15th treatment response nut or qq-p-416 type2 class 3 federal specification single treatment response nut

Specification Data:

76301-st3-725 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.