

View Online at <https://aerobasegroup.com/nsn/5310-01-028-4843>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Lubrication:**

Dry film lubricant

**Nut Style:**

Hexagon

**Nut Height:**

0.284 inches

**Width Across Flats:**

Between 0.553 inches and 0.564 inches

**Tempurature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

Between 36.0 rockwell c and 44.0 rockwell c

**Thread Size:**

0.375 inches

**Bearing Surface Type:**

Chamfered or washer faced

**Material:**

Steel comp 8740 or steel comp 4130 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-18729 military specification 2nd material response or mil-s-5000 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6049 spec.