

View Online at <https://aerobasegroup.com/nsn/5310-01-030-2671>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Pilot Diameter:**

Between 0.212 inches and 0.217 inches

**Pilot Length:**

0.192 inches

**Lubrication:**

Dry film lubricant

**Nut Height:**

0.381 inches

**Width Across Flats:**

0.295 inches

**Thread Series:**

Unc

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Material:**

Steel comp 1050 or steel comp 1055 or steel comp 1060 or steel comp 1064 or steel comp 1065 or steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1085 or steel comp 1095 or iron alloy 660

**Material Specification:**

Astm a682, grade 1050 to 1095 assn standard 1st material response or nas 5732 assn standard 2nd material response or mil-s-23915 comp 304 military specification 3rd material response

**Surface Treatment:**

Cadmium or passivate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification 1st treatment response or qq-p-35 federal specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-s-23915 spec.