## NSN 5310-01-037-4219

N/a

No Fiig: A021a0

**Unit Of Measure:** 

**Demilitarization:** 

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-037-4219 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Washer Outside Diameter:** 0.760 inches **Counterbore Diameter:** 0.474 inches nut and 0.484 inches nut **Overall Height:** Between 0.383 inches and 0.403 inches **Nut Style:** Flat with turned up edge **Nut Counterbore Depth:** 0.072 inches nut and 0.087 inches nut Width Across Flats: Between 0.492 inches and 0.512 inches **Thread Series:** Unif Thready Qty Per Inch (tpi): 20 Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Thread Size:** 0.438 inches Material: Steel comp e4340 nut or steel comp 4340 nut or steel comp 8740 nut **Material Specification:** Mil-s-5000 military specification 1st material response nut or mil-s-5000 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life:

## NSN 5310-01-037-4219

Assembled Washer Self-locking Nut - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.